

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260025
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-616-4789
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

P/N 2600-25 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.292 Inches Minimum And 1.307 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.750 Inches Minimum And 0.779 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.