

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260027
Minimum Qty (MOQ):	15 EA
NSN:	5325-00-641-0380
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-27 Specifications

Diameter:	0.303 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.329 Inches Nominal
Eyelet Outside Diameter:	0.247 Inches Nominal
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.780 Inches Minimum And 0.839 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.093 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.