

Description

corrosion resistant steel, slotted recess, total panel thickness 0.060

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126007-2](#)

SKU / Model:	26002S
Minimum Qty (MOQ):	5
NSN:	5325-00-584-0024
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2600-2S Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.572 Inches Minimum And 0.588 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.060 Inches Minimum And 0.089 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Comp 302 Ejector Spring Or Steel Corrosion Resisting Ejector Spring
Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material:	Steel Comp 302 Pin Or Steel Corrosion Resisting Pin
Material:	Steel Comp 305 Eyelet
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Ejector Spring Or 71321 Cagec,type 384 Mfr Ref 2nd Material Response Ejector Spring
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Pin Or 71321 Cagec,type 384 Mfr Ref 2nd Material Response Pin
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Stud Or 71321 Cagec,type 384 Mfr Ref 2nd Material Response Stud
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-2S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.