

**Description**

winged, cadmium steel

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	26002W
Minimum Qty (MOQ):	5
NSN:	5325-00-282-7458
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2600-2W Specifications

<b>Head Length:</b>	0.720 Inches Nominal
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Head Style:</b>	Fillister Wing
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.581 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.069 Inches Minimum And 0.089 Inches Maximum
<b>Stud Head Height:</b>	0.440 Inches Nominal
<b>Material:</b>	Steel Comp 1009 Eyelet
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Astm A109 Assn Std Single Material Response Eyelet
<b>Material Document And Classification:</b>	Astm A228 Assn Std Single Material Response Ejector Spring
<b>Material Document And Classification:</b>	Astm A228 Assn Std Single Material Response Pin
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Stud
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener receptacle from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-2W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.