

Description

winged, cadmium steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 26002W |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-282-7458 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 2600-2W Specifications

| | |
|--|---|
| Head Length: | 0.720 Inches Nominal |
| Securing Device Type: | Ring |
| Turnlock Stud Head Style: | Fillister Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.581 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.069 Inches Minimum And 0.089 Inches Maximum |
| Stud Head Height: | 0.440 Inches Nominal |
| Material: | Steel Comp 1009 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Material Document And Classification: | Astm A109 Assn Std Single Material Response Eyelet |
| Material Document And Classification: | Astm A228 Assn Std Single Material Response Ejector Spring |
| Material Document And Classification: | Astm A228 Assn Std Single Material Response Pin |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Stud |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener receptacle from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-2W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.