

P/N 2600-3

Description

total panel thickness: 0.090", cadmium plated steel, slotted recess, camloc, quarterturn, 1/4 stud, 2600 series stud

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

1126000-3

SKU / Model: 26003

Minimum Qty (MOQ): 10

NSN: 5325-00-282-0624

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 094533, Eyelets Or Eyelet Hooks Noi









P/N 2600-3 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Diameter:	0.296 IIICHES MITHITIUM AND 0.506 IIICHES MAXIMUM
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.602 Inches Minimum And 0.617 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.060 Inches Minimum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material Document And Classification:	Astm A322 Assn Std Single Material Response Stud Or Astm A331 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+studs/2600-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.