

**Description**

total panel thickness: 0.090", cadmium plated steel, slotted recess, camloc, quarterturn, 1/4 stud, 2600 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126000-3](#)

SKU / Model:	26003
Minimum Qty (MOQ):	10
NSN:	5325-00-282-0624
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	094533, Eyelets Or Eyelet Hooks Noi



\* See page 2 for technical characteristics

## P/N 2600-3 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.602 Inches Minimum And 0.617 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.060 Inches Minimum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 1009 Eyelet
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Astm A322 Assn Std Single Material Response Stud Or Astm A331 Assn Std Single Material Response Stud
<b>Material Document And Classification:</b>	Qq-s-633 Fed Spec Single Material Response Eyelet
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Pin
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2600-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.