

Description

total panel thickness: 0.090", cadmium plated steel, slotted recess, camloc, quarterturn, 1/4 stud, 2600 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126000-3](#)

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | 26003 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-282-0624 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 094533, Eyelets Or Eyelet Hooks Noi |



* See page 2 for technical characteristics

P/N 2600-3 Specifications

| | |
|--|--|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.602 Inches Minimum And 0.617 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.060 Inches Minimum |
| Drive Type: | Slotted |
| Material: | Steel Comp 1009 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Pin |
| Material Document And Classification: | Astm A322 Assn Std Single Material Response Stud Or Astm A331 Assn Std Single Material Response Stud |
| Material Document And Classification: | Qq-s-633 Fed Spec Single Material Response Eyelet |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2600-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.