

**Description**

1/4 Turn Stud part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | 26003W                                 |
| Minimum Qty (MOQ):      | 5 EA                                   |
| NSN:                    | 5325-00-298-7003                       |
| Schedule B:             | 7318.15.5030                           |
| ECCN:                   | EAR99                                  |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 2600-3W Specifications

|  |   |
|--|---|
| <b>Head Length:</b>  | 0.700 Inches Minimum And 0.740 Inches Maximum |
| <b>Turnlock Stud Head Style:</b>   | Flat Fillister Wing                           |
| <b>Stud Assembly Style:</b>  | Stud Assembly                                 |
| <b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b> | 0.602 Inches Minimum And 0.617 Inches Maximum |
| <b>Eyelet Outside Diameter:</b>  | 0.244 Inches Minimum And 0.250 Inches Maximum |
| <b>Eyelet Length:</b>  | 0.322 Inches Nominal                          |
| <b>Material Accommodated Thickness:</b>                                  | 0.060 Inches Minimum And 0.119 Inches Maximum |
| <b>Stud Head Height:</b>   | 0.360 Inches Minimum And 0.400 Inches Maximum |
| <b>Material:</b>   | Steel Overall                                 |
| <b>Surface Treatment:</b>  | Cadmium Overall And Chromate Overall          |

## How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-3W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.