

Description

1/4 Turn Stud part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | 26003W |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5325-00-298-7003 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-3W Specifications

| | |
|--|---|
| Head Length: | 0.700 Inches Minimum And 0.740 Inches Maximum |
| Turnlock Stud Head Style: | Flat Fillister Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.602 Inches Minimum And 0.617 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.060 Inches Minimum And 0.119 Inches Maximum |
| Stud Head Height: | 0.360 Inches Minimum And 0.400 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-3W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.