

**Description**

total panel thickness: 0.120", cadmium plated steel, slotted recess, camloc, quarterturn, 1/4 turn, 2600 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126000-4](#)

SKU / Model:	26004
Minimum Qty (MOQ):	10
NSN:	5325-01-179-7415
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N 2600-4 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.609 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.120 Inches Minimum And 0.149 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.088 Inches Minimum And 0.098 Inches Maximum
<b>Material:</b>	Steel Ejector Springsteel Comp 1009 Eyeletsteel Pinsteel Comp 4037 Stud
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Ejector Springastm A109 Assn Std Single Material Response Eyeletastm A228 Assn Std Single Material Response Pinastm A547 Assn Std Single Material Response Stud
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.