

# **P/N 2600-5SW**

## **Description**

corrosion resistant steel, winged, total panel thickness 0.150" - 0.179

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

## 1126014-5

SKU / Model: 26005SW

Minimum Qty (MOQ): 2

NSN: 5325-00-810-8509

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 2600-5SW Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.662 Inches Minimum And 0.677 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.539 Inches Maximum
Stud Head Height:	0.480 Inches Minimum And 0.520 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 304 Eyelet
Material:	Steel Comp 302 Pin
Surface Treatment:	Passivate Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-5SW">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-5SW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.