

**Description**

total panel thickness 0.180" - 0.209", corrosion resistant steel, slotted recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126007-6](#)

SKU / Model:	26006S
Minimum Qty (MOQ):	10
NSN:	5325-00-543-3410
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2600-6S Specifications

<b>Diameter:</b>	0.308 Inches Nominal
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.692 Inches Minimum And 0.707 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.180 Inches Minimum And 0.209 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-6S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.