

Description

cadmium plated steel - slotted recess, total panel thickness: 0.210" - 0.239"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	26007
Minimum Qty (MOQ):	10
NSN:	5325-00-290-3972



P/N 2600-7 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.722 Inches Minimum And 0.737 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.239 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material Document And Classification:	Astm A322 Assn Std Single Material Response Stud Or Astm A331 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-s-640 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this camloc, 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.