



[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N 2600-7W**

## Description

total panel thickness 0.21" - 0.239", (sold only in stainless steel see replacement number), corrosion resistant steel, winged, 2600 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[1126010-7](#)

SKU / Model:	26007W
Minimum Qty (MOQ):	5
NSN:	5325-00-298-7005
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



# P/N 2600-7W Specifications

Head Length:	0.720 Inches Nominal
Turnlock Stud Head Style:	Flat Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.722 Inches Minimum And 0.737 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.239 Inches Maximum
Stud Head Height:	0.440 Inches Nominal
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-7W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.