

Description

total panel thickness 0.24", corrosion resistant steel, slotted recess, 2600 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126007-8](#)

SKU / Model:	26008S
Minimum Qty (MOQ):	5
NSN:	5325-00-550-0711
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2600-8S Specifications

Diameter:	0.302 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.752 Inches Minimum And 0.767 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.210 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.093 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-8S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.