

**Description**

total panel thickness 0.24", corrosion resistant steel, slotted recess, 2600 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126007-8](#)

|                         |  |
|-------------------------|--|
| SKU / Model:            | 26008S                                 |
| Minimum Qty (MOQ):      | 5                                      |
| NSN:                    | 5325-00-550-0711                       |
| ECCN:                   | EAR99                                  |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



\* See page 2 for technical characteristics

# P/N 2600-8S Specifications

|   |   |
|---|---|
| Diameter:   | 0.302 Inches Nominal                          |
| Securing Device Type:   | Washer  |
| Turnlock Stud Head Style:   | Flat Fillister                                |
| Stud Assembly Style:  | Stud Assembly                                 |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.752 Inches Minimum And 0.767 Inches Maximum |
| Eyelet Outside Diameter:  | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length:  | 0.322 Inches Nominal                          |
| Material Accommodated Thickness:                                  | 0.210 Inches Minimum And 0.269 Inches Maximum |
| Drive Type:   | Slotted                                       |
| Stud Head Height:   | 0.093 Inches Nominal                          |
| Material:   | Steel Overall                                 |
| Surface Treatment:  | Passivate Overall                             |

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-8S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.