

Description

total panel thickness 0.24", corrosion resistant steel, slotted recess, 2600 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126007-8](#)

| | |
|-------------------------|--|
| SKU / Model: | 26008S |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-550-0711 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 2600-8S Specifications

| | |
|--|---|
| Diameter: | 0.302 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.752 Inches Minimum And 0.767 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.210 Inches Minimum And 0.269 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.093 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-8S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.