

Description

corrosion resistant steel - winged - total panel thickness 0.240" - 0.269", (sold only in stainless steel see replacement number)

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 26008W |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5325-00-639-5575 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

P/N 2600-8W Specifications

| | |
|--|---|
| Head Length: | 0.725 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Flat Fillister Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.758 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.210 Inches Minimum And 0.269 Inches Maximum |
| Stud Head Height: | 0.440 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-8W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.