

P/N 2600-9

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | 26009 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5325-00-489-0928 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |



^{*} See page 2 for technical characteristics

P/N 2600-9 Specifications

| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
|---|---|
| Securing Device Type: | Spring |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.782 Inches Minimum And 0.797 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.240 Inches Minimum And 0.299 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this 1/4 turn stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.