

**Description**

panel thickness 0.27" - 0.299", corrosion resistant steel, winged,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126014-9](#)

SKU / Model:	26009SW
Minimum Qty (MOQ):	5
NSN:	5325-00-682-1637
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2600-9SW Specifications

<b>Head Length:</b>	0.700 Inches Minimum And 0.740 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister Wing
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.782 Inches Minimum And 0.797 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.270 Inches Minimum And 0.299 Inches Maximum
<b>Stud Head Height:</b>	0.360 Inches Minimum And 0.400 Inches Maximum
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 304 Eyelet
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Ejector Spring
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-9SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.