

Description

panel thickness 0.27" - 0.299", corrosion resistant steel, winged,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1126014-9](#)

SKU / Model:	26009SW
Minimum Qty (MOQ):	5
NSN:	5325-00-682-1637
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2600-9SW Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
Turnlock Stud Head Style:	Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.782 Inches Minimum And 0.797 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.270 Inches Minimum And 0.299 Inches Maximum
Stud Head Height:	0.360 Inches Minimum And 0.400 Inches Maximum
Material:	Steel Comp 302 Stud
Material:	Steel Comp 304 Eyelet
Material:	Steel Comp 302 Pin
Material:	Steel Ejector Spring
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-9SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.