

## Description

corrosion resistant steel - winged - total panel thickness 0.270" - 0.299", (sold only in stainless steel see replacement number)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	26009W
Minimum Qty (MOQ):	2
NSN:	5325-00-514-6490
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

# P/N 2600-9W Specifications

Head Length:	0.720 Inches Nominal
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.782 Inches Minimum And 0.797 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.240 Inches Minimum And 0.299 Inches Maximum
Stud Head Height:	0.440 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-9W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.