

P/N 26S51-14

Description

total panel thickness 0.42" - 0.449", corrosion resistant steel, philips recess, camloc, 26S51 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

1126008-14

SKU / Model: 26S5114

Minimum Qty (MOQ): 2

NSN: 5325-00-256-3748

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









P/N 26S51-14 Specifications

Diameter: 0.298 Inches Minimum And 0.308 Inches Maximum Securing Device Type: Spring Turnlock Stud Head Style: Fillister Stud Assembly Style: Stud Assembly Distance From Engaging Member To Largest Bearing Surface of Head: 0,941 Inches Nominal Eyelet Outside Diameter: 0.244 Inches Minimum And 0.250 Inches Maximum Eyelet Length: 0.322 Inches Nominal Material Accommodated Thickness: 0.420 Inches Minimum And 0.449 Inches Maximum Drive Type: Cross Recess Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Event Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material Document And Classification: Steel Comp 305 Eyelet Material Document And Classification: Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Eyelet Surface Treatment: Qq-y-35		
Turnlock Stud Head Style: Stud Assembly Style: Stud Assembly Style: Distance From Engaging Member To Largest Bearing Surface Of Head: Stylet Outside Diameter: Eyelet Outside Diameter: Eyelet Length: Material Accommodated Thickness: O.424 Inches Minimum And 0.250 Inches Maximum Eyelet Compadiated Thickness: O.420 Inches Minimum And 0.449 Inches Maximum Orive Type: Cross Recess Material: Material: Steel Comp 302 Ejector Spring Material: Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Mat	Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Stud Assembly Style: Distance From Engaging Member To Largest Bearing Surface Of Head: Eyelet Outside Diameter: 0.244 Inches Minimum And 0.250 Inches Maximum Eyelet Length: 0.322 Inches Nominal Material Accommodated Thickness: 0.420 Inches Minimum And 0.449 Inches Maximum Drive Type: Cross Recess Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material: Material: Steel Comp 305 Eyelet Material: Material Document And Classification: Material Document And Classification: Qq-w-423 Fed Spec Ist Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Securing Device Type:	Spring
Distance From Engaging Member To Largest Bearing Surface Of Head: Eyelet Outside Diameter: Eyelet Cutside Diameter: O.244 Inches Minimum And 0.250 Inches Maximum Eyelet Length: O.322 Inches Nominal Material Accommodated Thickness: O.420 Inches Minimum And 0.449 Inches Maximum Drive Type: Cross Recess Material: Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Material: Steel Comp 302 Pin Material: Steel Comp 305 Eyelet Material Document And Classification: Material Document And Classification: Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Turnlock Stud Head Style:	Fillister
Head: Eyelet Outside Diameter: O.244 Inches Minimum And 0.250 Inches Maximum Eyelet Length: O.322 Inches Nominal Material Accommodated Thickness: O.420 Inches Minimum And 0.449 Inches Maximum Drive Type: Cross Recess Material: Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material: Material: Oq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Stud Assembly Style:	Stud Assembly
Eyelet Length: 0.322 Inches Nominal Material Accommodated Thickness: 0.420 Inches Minimum And 0.449 Inches Maximum Drive Type: Cross Recess Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material: Steel Comp 305 Eyelet Material Document And Classification: Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall		f 0.941 Inches Nominal
Material Accommodated Thickness: D.420 Inches Minimum And 0.449 Inches Maximum Cross Recess Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material: Steel Comp 305 Eyelet Material Document And Classification: Material Document And Classification: Material Document And Classification: Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Drive Type: Material: Steel Comp 302 Ejector Spring Material: Steel Comp 302 Stud Or Steel Corrosion Resisting Stud Material: Steel Comp 302 Pin Material: Steel Comp 305 Eyelet Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Eyelet Length:	0.322 Inches Nominal
Material:Steel Comp 302 Ejector SpringMaterial:Steel Comp 302 Stud Or Steel Corrosion Resisting StudMaterial:Steel Comp 302 PinMaterial:Steel Comp 305 EyeletMaterial Document And Classification:Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response StudMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response Ejector SpringMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Material Accommodated Thickness:	0.420 Inches Minimum And 0.449 Inches Maximum
Material:Steel Comp 302 Stud Or Steel Corrosion Resisting StudMaterial:Steel Comp 302 PinMaterial:Steel Comp 305 EyeletMaterial Document And Classification:Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response StudMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response Ejector SpringMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Drive Type:	Cross Recess
Material:Steel Comp 302 PinMaterial:Steel Comp 305 EyeletMaterial Document And Classification:Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response StudMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response Ejector SpringMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Material:	Steel Comp 302 Ejector Spring
Material:Steel Comp 305 EyeletMaterial Document And Classification:Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response StudMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response Ejector SpringMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material Document And Classification:Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response StudMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response Ejector SpringMaterial Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Material:	Steel Comp 302 Pin
Material Document And Classification: Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Ejector Spring Material Document And Classification: Qq-w-423 Fed Spec Single Material Response Pin Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Material:	Steel Comp 305 Eyelet
Material Document And Classification:Qq-w-423 Fed Spec Single Material Response PinMaterial Document And Classification:Qq-s-766 Fed Spec Single Material Response EyeletSurface Treatment:Passivate Overall	Material Document And Classification:	
Material Document And Classification: Qq-s-766 Fed Spec Single Material Response Eyelet Surface Treatment: Passivate Overall	Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Ejector Spring
Surface Treatment: Passivate Overall	Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Pin
	Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S51-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.