

P/N 26S51-16

Description

Diameter: 19/64", steel comp 305 eyelet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

26S5116 SKU / Model:

Minimum Qty (MOQ):

NSN: 5325-00-843-7591

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









P/N 26S51-16 Specifications

| - | |
|---|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Securing Device Type: | Spring |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | f 1.001 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.332 Inches Nominal |
| Material Accommodated Thickness: | 0.480 Inches Minimum And 0.509 Inches Maximum |
| Drive Type: | Cross Recess |
| Material: | Steel Comp 302 Ejector Spring |
| Material: | Steel Comp 302 Stud Or Steel Corrosion Resisting Stud |
| Material: | Steel Comp 302 Pin |
| Material: | Steel Comp 305 Eyelet |
| Material Document And Classification: | Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud |
| Material Document And Classification: | Qq-w-423 Fed Spec Single Material Response Pin |
| Material Document And Classification: | Qq-s-766 Fed Spec Single Material Response Eyelet |
| Material Document And Classification: | Wqq-w-423 Fed Spec Single Material Response Ejector Spring |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S51-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.