

Description

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 26S5117 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5325-00-255-7282 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 26S51-17 Specifications

| | |
|--|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Securing Device Type: | Spring |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 1.031 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.510 Inches Minimum And 0.539 Inches Maximum |
| Drive Type: | Cross Recess |
| Material: | Steel Comp 302 Ejector Spring |
| Material: | Steel Comp 302 Stud Or Steel Corrosion Resisting Stud |
| Material: | Steel Comp 302 Pin |
| Material: | Steel Comp 305 Eyelet |
| Material Document And Classification: | Qq-w-423 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagac 81321 Mfr Ref 2nd Material Response Stud |
| Material Document And Classification: | Qq-w-423 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-423 Fed Spec Single Material Response Pin |
| Material Document And Classification: | Qq-s-766 Fed Spec Single Material Response Eyelet |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S51-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.