

P/N 26S51-4

Description

total panel thickness 0.12" - 0.149", corrosion resistant steel, philips recess, 26S51 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

1126008-4

SKU / Model: 26S514

Minimum Qty (MOQ): 10

NSN: 5325-00-882-5030

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









P/N 26S51-4 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.641 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.332 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.149 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Material Document And Classification:	Qq-w-423 Fed Spec 1st Material Response Stud Or Comp 384,cagec 71321 Mfr Ref 2nd Material Response Stud
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Pin
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S51-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.