

## P/N 26S8-1

## **Description**

Diameter: 1/4", steel overall

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 26S81

Minimum Qty (MOQ): 5

NSN: 5325-00-797-3002

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









# **P/N 26S8-1 Specifications**

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.542 Inches Minimum And 0.557 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.030 Inches Minimum And 0.419 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2658-1">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2658-1</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.