

P/N 2658-1

Military-Fasteners.com

#### Description

Diameter: 1/4", steel overall

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | 26581                                  |
|-------------------------|--|
| Minimum Qty (MOQ):      | 5                                      |
| NSN:                    | 5325-00-797-3002                       |
| Schedule B:             | 7318.15.5030                           |
| ECCN:                   | EAR99                                  |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



# P/N 26S8-1 Specifications

| Diameter:   | 0.251 Inches Minimum And 0.256 Inches Maximum |
|---|---|
| Turnlock Stud Head Style:   | Flat Fillister                                |
| Stud Assembly Style:  | Stud Assembly                                 |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.542 Inches Minimum And 0.557 Inches Maximum |
| Eyelet Outside Diameter:  | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length:  | 0.322 Inches Nominal                          |
| Material Accommodated Thickness:                                  | 0.030 Inches Minimum And 0.419 Inches Maximum |
| Drive Type:   | Cross Recess                                  |
| Stud Head Height:   | 0.069 Inches Minimum And 0.076 Inches Maximum |
| Material:   | Steel Overall                                 |
| Surface Treatment:  | Cadmium Overall                               |

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <u>https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2658-1</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.