

**Description**

26S8-14 Turnlock Fastener Stud Assembly

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | 26S814                                 |
| Minimum Qty (MOQ):      | 10                                     |
| NSN:                    | 5325-01-131-1722                       |
| Schedule B:             | 7318.15.5030                           |
| ECCN:                   | EAR99                                  |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 26S8-14 Specifications

|  |   |
|--|---|
| <b>Diameter:</b>   | 0.298 Inches Minimum And 0.308 Inches Maximum |
| <b>Securing Device Type:</b>   | Washer  |
| <b>Turnlock Stud Head Style:</b>   | Flat Fillister                                |
| <b>Stud Assembly Style:</b>  | Stud Assembly                                 |
| <b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b> | 0.750 Inches Minimum And 0.782 Inches Maximum |
| <b>Eyelet Outside Diameter:</b>  | 0.244 Inches Minimum And 0.250 Inches Maximum |
| <b>Eyelet Length:</b>  | 0.322 Inches Nominal                          |
| <b>Drive Type:</b>   | Cross Recess                                  |
| <b>Stud Head Height:</b>   | 0.056 Inches Minimum And 0.066 Inches Maximum |
| <b>Material:</b>   | Steel Overall                                 |
| <b>Surface Treatment:</b>  | Cadmium Overall                               |

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.