

**Description**

panel thickness 0.450" - 0.479", cadmium plated steel, philips recess, 26S8 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126004-15](#)

SKU / Model:	26S815
Minimum Qty (MOQ):	5
NSN:	5325-00-941-6473
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 26S8-15 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.962 Inches Minimum And 0.977 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.450 Inches Minimum And 0.479 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Chromium Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.