

Description

total panel thickness 0.480" - 0.509", cadmium plated steel, philips recess, 26S8 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126004-16](#)

SKU / Model:	26S816
Minimum Qty (MOQ):	5
NSN:	5325-00-215-0457
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 26S8-16 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.960 Inches Nominal
Eyelet Outside Diameter:	0.246 Inches Nominal
Eyelet Length:	0.320 Inches Nominal
Drive Type:	Cross Recess
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.