

**Description**

cadmium plated steel philips recess - total panel thickness 0.510" - 0.539

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126004-17](#)

SKU / Model:	26S817
Minimum Qty (MOQ):	10
NSN:	5325-00-514-9369
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



## P/N 26S8-17 Specifications

<b>Diameter:</b>	0.303 Inches Nominal
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.441 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.247 Inches Nominal
<b>Eyelet Length:</b>	0.332 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.510 Inches Minimum And 0.539 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.