



★ FASTENERS

Military-Fasteners.com

P/N 26S8-2

Description

total panel thickness 0.060" - 0.089", cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1126004-2](#)

SKU / Model:	26S82
Minimum Qty (MOQ):	10
NSN:	5325-00-689-8837
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 26S8-2 Specifications

Diameter:	0.303 Inches Nominal
Turnlock Stud Head Style:	Fillister Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.572 Inches Minimum And 0.587 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.030 Inches Minimum And 0.089 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.093 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.