

## Description

Diameter: 19/64", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	26S820
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-775-6461
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 26S8-20 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	1.112 Inches Minimum And 1.127 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.600 Inches Minimum And 0.629 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.