

Description

cadmium plated steel philips recess, total panel thickness 0.090" - 0.119

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126004-3](#)

| | |
|-------------------------|--|
| SKU / Model: | 26S83 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-726-6699 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 26S8-3 Specifications

| | |
|--|---|
| Diameter: | 0.303 Inches Nominal |
| End Item Identification: | W/s:tactical Air Opns Module (an/tyq-(23); Aircraft, C-18a, Ec-18b; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, C-2a (reprocured); Aircraft, Airlifter C-17a; Helicopter, Search And Rescue, Hh-60h; Helicopter, Hh-53h Pave Low; Helicopter, Mh-53e; Helicopter, Carrier Based Asw, Sh-60f |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.602 Inches Minimum And 0.617 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.060 Inches Minimum And 0.119 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.093 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this turnlock fasteners stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.