

Description

total panel thickness 0.12" - 0.149", cadmium plated steel philips recess, camloc

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126004-4](#)

| | |
|-------------------------|----------------------------------------|
| SKU / Model: | 26S84 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-703-9346 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 26S8-4 Specifications

| | |
|--------------------------------------------------------------------------|-----------------------------------------------|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Fillister Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.640 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.090 Inches Minimum And 0.149 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.093 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.