

## Description

total panel thickness 0.12" - 0.149", cadmium plated steel philips recess, camloc

\* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

## Additional Information

### Alternate Part Numbers

[1126004-4](#)

SKU / Model:	26S84
Minimum Qty (MOQ):	10
NSN:	5325-00-703-9346
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



# P/N 26S8-4 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.640 Inches Nominal
Eyelet Outside Diameter:	0.247 Inches Nominal
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.090 Inches Minimum And 0.149 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.093 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.