

**Description**

total panel thickness 0.240" - 0.269", cadmium plated steel, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1126004-8](#)

SKU / Model:	26S88
Minimum Qty (MOQ):	10
NSN:	5325-00-687-5689
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 26S8-8 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>End Item Identification:</b>	1520-01-035-0266 Helicopter, Utility
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.752 Inches Minimum And 0.767 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.240 Inches Minimum And 0.269 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Stud Head Height:</b>	0.088 Inches Minimum And 0.098 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Stud Assembly, Turnlock
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Eyelet
<b>Material Document And Classification:</b>	Qq-s-640 Fed Spec Single Material Response Eyelet
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Ejector Spring
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.