

Description

total panel thickness 0.240" - 0.269", cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1126004-8](#)

SKU / Model:	26S88
Minimum Qty (MOQ):	10
NSN:	5325-00-687-5689
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 26S8-8 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
End Item Identification:	1520-01-035-0266 Helicopter, Utility
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.752 Inches Minimum And 0.767 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.240 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Part Name Assigned By Controlling Agency:	Stud Assembly, Turnlock
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Eyelet
Material Document And Classification:	Qq-s-640 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/26S8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.