

# P/N 2700-11S

### **Description**

Diameter: 1/4", steel comp 305 eyelet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 270011S

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-045-1875

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 2700-11S Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.761 Inches Minimum And 0.771 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.300 Inches Minimum And 0.359 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

# **How to Order**

Order this 1/4 turn stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-11S">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-11S</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-11S">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-11S</a> and selecting the