

Description

Diameter: 1/4", steel lockspring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	270015
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-202-1474
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2700-15 Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.881 Inches Minimum And 0.891 Inches Maximum
Eyelet Outside Diameter:	0.250 Inches Minimum And 0.328 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.420 Inches Minimum And 0.479 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Lockspring
Material:	Steel Pin
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.