

# P/N 2700-16S

### **Description**

Diameter: 1/4", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 270016S

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-849-7014

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 2700-16S Specifications

Diameter:	0.244 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.911 Inches Minimum And 0.921 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.450 Inches Minimum And 0.509 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this 1/4 turn stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-16S</a> and selecting the