

Description

panel thickness 0.150" - 0.179", corrosion resistant steel, slotted recess, quarterturn, 2700 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1127003-5](#)

SKU / Model:	27005S
Minimum Qty (MOQ):	10
NSN:	5325-00-849-8512
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2700-5S Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.581 Inches Minimum And 0.591 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.179 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-5S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.