

Description

corrosion resistant steel - slotted recess - total panel thickness 0.180"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	27006S
Minimum Qty (MOQ):	10
NSN:	5325-00-646-7300
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2700-6S Specifications

<b>Diameter:</b>	0.251 Inches Minimum And 0.256 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Stud Head
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.611 Inches Minimum And 0.621 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.328 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.150 Inches Minimum And 0.209 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.069 Inches Minimum And 0.076 Inches Maximum
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-6S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.