

Description

Diameter: 1/4", steel comp 305 eyelet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	27007S
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-787-8677
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	094540, Fasteners Brass / Bronze / Copper

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2700-7S Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.641 Inches Minimum And 0.651 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.239 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-7S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.