

# P/N 2700-8

### **Description**

Diameter: 1/4", steel overall

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	27008
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-171-4237
Schedule B:	7318.15.5030
FCCN:	FARQQ



<sup>\*</sup> See page 2 for technical characteristics

## **P/N 2700-8 Specifications**

Diameter:	0.253 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.671 Inches Minimum And 0.681 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.240 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.072 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## **How to Order**

Order this 1/4 turn stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2700-8</a> and selecting the