

P/N 27S3-1

Military-Fasteners.com

Description

Panel thickness 0.03" - 0.059", cadmium plated steel, philips recess, 27S3 series stud

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	27S31
Minimum Qty (MOQ):	10
NSN:	5325-00-814-6749
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



P/N 27S3-1 Specifications

Diameter:	0.244 Inches Minimum And 0.256 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.461 Inches Minimum And 0.471 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.030 Inches Minimum And 0.419 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <u>https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2753-1</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.