

Description

total panel thickness 0.300" - 0.329", cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1127004-10](#)

SKU / Model:	27S310
Minimum Qty (MOQ):	5
NSN:	5325-00-413-0121
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 27S3-10 Specifications

Diameter:	0.250 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.736 Inches Nominal
Eyelet Outside Diameter:	0.247 Inches Nominal
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.300 Inches Minimum And 0.329 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.073 Inches Nominal
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Eyelet
Material Document And Classification:	Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Surface Treatment:	Cadmium Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/27S3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.