

Description

total panel thickness 0.300" - 0.329", cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1127004-10](#)

| | |
|-------------------------|--|
| SKU / Model: | 27S310 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-413-0121 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 27S3-10 Specifications

| | |
|--|--|
| Diameter: | 0.250 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.736 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.300 Inches Minimum And 0.329 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.073 Inches Nominal |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Eyelet |
| Material Document And Classification: | Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/27S3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.